

Datasheet

RELAX GLASS IRA IP65



Code	Wattage	Material	Color	EAN	IP	Dimensions WxHxD in cm	Weight in g	Features	Cable	Connection	Heat-able m ²	Mounting
BRELG1500-3	1,5 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Silver <u>Front:</u> Black	4260409695382	65	90 x 17 x 8	5100	ON-/ OFF-Switch	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	7	Wall and ceiling
BRELG1500-3W	1,5 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Silver <u>Front:</u> White	4260409695856	65	90 x 17 x 8	5100	ON-/ OFF-Switch	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	7	Wall and ceiling
BRELG1500-1	1,5 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Black <u>Front:</u> Black	4260409695764	65	90 x 17 x 8	5100	ON-/ OFF-Switch	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	7	Wall and ceiling
BRELG1800-3	1,8 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Silver <u>Front:</u> Black	4260409695375	65	90 x 17 x 8	5100	ON-/ OFF-Switch	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	8,4	Wall and ceiling

Code	Wattage	Material	Color	EAN	IP	Dimensions WxHxD in cm	Weight in g	Features	Cable	Connection	Heat- able m ²	Mounting
BRELG1800-3W	1,8 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Silver <u>Front:</u> White	4260409695863	65	90 x 17 x 8	5100	ON-/ OFF- Switch	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	8,4	Wall and ceilling
BRELG1800-1	1,8 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Black <u>Front:</u> Black	4260409695771	65	90 x 17 x 8	5100	ON-/ OFF- Switch	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	8,4	Wall and ceilling
BRELG2200-3	2,2 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Silver <u>Front:</u> Black	4260409695368	65	90 x 17 x 8	5100	ON-/ OFF- Switch	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	9,6	Wall
BRELG2200-3W	2,2 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Silver <u>Front:</u> White	4260409695870	65	90 x 17 x 8	5100	ON-/ OFF- Switch	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	9,6	Wall
BRELG2200-1	2,2 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Black <u>Front:</u> Black	4260409695788	65	90 x 17 x 8	5100	ON-/ OFF- Switch	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	9,6	Wall

RELAX GLASS IRA IP65 with dimmer & remote control

Code	Wattage	Material	Color	EAN	IP	Dimensions BxHxT in cm	Weight in g	Features	Cable	Connection	Heat-able m ²	Mounting
BRELG1500RD-3	1,5 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Silver <u>Front:</u> Black	4260409695443	65	90 x 17 x 8	5200	ON/OFF switch & remote control with 1-2 or 3 hours-timer & integrated dimmer 3-stage (33/66/100%)	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	7	Wall and ceiling
BRELG1500RD-3W	1,5 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Silver <u>Front:</u> White	4260409695818	65	90 x 17 x 8	5200	ON/OFF switch & remote control with 1-2 or 3 hours-timer & integrated dimmer 3-stage (33/66/100%)	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	7	Wall and ceiling
BRELG1500RD-1	1,5 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Black <u>Front:</u> Black	4260409695450	65	90 x 17 x 8	5200	ON/OFF switch & remote control with 1-2 or 3 hours-timer & integrated dimmer 3-stage (33/66/100%)	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	7	Wall and ceiling
BRELG1800RD-3	1,8 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Silver <u>Front:</u> Black	4260409695429	65	90 x 17 x 8	5200	ON/OFF switch & remote control with 1-2 or 3 hours-timer & integrated dimmer 3-stage (33/66/100%) (33/66/100%)	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	8,4	Wall and ceiling

Code	Wattage	Material	Color	EAN	IP	Dimensions BxHxT in cm	Weight in g	Features	Cable	Connection	Heat-able m ²	Mounting
BRELG1800RD-3W	1,8 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Silver <u>Front:</u> White	4260409695825	65	90 x 17 x 8	5200	ON/OFF switch & remote control with 1-2 or 3 hours-timer & integrated dimmer 3-stage (33/66/100%)	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	8,4	Wall and ceiling
BRELG1800RD-1	1,8 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Black <u>Front:</u> Black	4260409695436	65	90 x 17 x 8	5200	ON/OFF switch & remote control with 1-2 or 3 hours-timer & integrated dimmer 3-stage (33/66/100%)	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	8,4	Wall and ceiling
BRELG2200RD-3	2,2 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Silver <u>Front:</u> Black	4260409695405	65	90 x 17 x 8	5200	ON/OFF switch & remote control with 1-2 or 3 hours-timer & integrated dimmer 3-stage (33/66/100%)	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	9,6	Wall
BRELG2200RD-3W	2,2 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Silver <u>Front:</u> White	4260409695832	65	90 x 17 x 8	5200	ON/OFF switch & remote control with 1-2 or 3 hours-timer & integrated dimmer 3-stage (33/66/100%)	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	9,6	Wall

Code	Wattage	Material	Color	EAN	IP	Dimensions BxHxT in cm	Weight in g	Features	Cable	Connection	Heat-able m ²	Mounting
BRELG2200RD-1	2,2 kW	<u>Casing:</u> Corrosion resistance anodized aluminum <u>Front:</u> SCHOTT NEXTREMA® ceramic glass	<u>Casing:</u> Black <u>Front:</u> Black	4260409695412	65	90 x 17 x 8	5200	ON/OFF switch & remote control with 1-2 or 3 hours-timer & integrated dimmer 3-stage (33/66/100%)	1,80m 3-wire 1,5 mm ² , Schuko plug	L/N/PE, 230-240V~ 50Hz	9,6	Wall
Remote control												
BRELGRD (for 1500-2200 W heater)		ABS Acrylnitril- Butadien-Styrol	Black	4260409695404		4,5 x 12,5	50	ON/OFF remote with 1-2 or 3 hours-timer & dimmer function 3-stage (33/66/100%)				